

ITEM : 20102832

Antistatic Stainless wrist band with coil cord

■ **Material components –**

◎ **Wrist band : Adjustable type (color: Light blue/yellow/Black)**

- A. Insulating ABS plastic.
- B. 4/7/10mm nickel plate brass stud. Fit to 4/7/10mm spring type socket.
- C. Stainless metal expansion band, inside links are constructed of 300 series Stainless steel. Outer chrome plate painted surface.
- D. Injection connect buckle



◎ **Ground cord (Color –light blue/ black)**

- A. 4/7/10mm Spring socket, copper with nickel.
- B. Resistor 1 meg ohms $\pm 5\%$, 1/4 watt series resistor limits current for operator safety.
- C. 2.3mm(D),#1 tinsel, consisting of 7 strands of polyester wrapped with copper. High flex life.
- D. Polyurethane wire insulation. Rapid retraction coil cord compresses length with Resulting benefit of less tangling and dragging along work surface.
- E. Barrel type banana plug with machined contour spring support. Crimped uniformly From 4 sides for maximum strength. Fits industry standard banana jack.
- F. PVC plastic material molded on. Banding life test Average > 50,000 cycle ANSI/ESD S20.20.
- G. Alligator clip –with nickel plated.

Gul och blå = beställningsvara
Svart = 20102832



- Wrist band Resistance : $10e3$ ohm
- Grounding resistance RTG : $10e6 \pm 10\%$ ohm
- Non-particle, clean room available.

DIREKTRONIK
Dataprodukter utöver det vanliga

info@direktronik.se

+46-852400700