



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. BRASS PER QQ-B-613
- 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 4. BERYLLIUM COPPER PER QQ-C-530
- 5. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 6. TEFLON MIL-P-19468

9	COVER	NOTE 2	NOTE 3	1	CV-523X06-T
8	INSULATOR	NOTE 6	NATURAL	1	SMA5072A2-9T-50
7	CONTACT PIN	NOTE 4	NOTE 5	1	SMA5990-8
6	GASKET	SILICONE	RED	1	GS-6/43X06
5	RETAINER RING	NOTE 4	NATURAL	1	SMA5000-4-B
4	CONTACT PIN	NOTE 1	NOTE 5	1	SMA1112A4-4-B
3	INSULATOR	NOTE 6	NATURAL	1	SMA1112A3-3T-50
2	HOUSING WITH BODY	NOTE 1	NOTE 3	1	SMA5072A2-2S-B
1	SHELL	NOTE 1	NOTE 3	1	SMA5000-1-C
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED TOLERANCES
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

PART NO. 20117496	
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'

DIREKTRONIK	
TITLE SMA MALE TO FEMALE R/A ADAPTOR	
DRAWING NO.	
ITEM NO.	

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	5/1	ISSUE	A	FILE NO
-----	-------------	----------	--------	------	-------------	-------	-----	-------	---	---------