


Dataprodukter utöver det vanliga


- Supports computer resolutions to 4K@120Hz or 8K@60Hz 4:4:4
- Plug and Play
- Support HDCP2.2
- Self-detecting function for EDID information
- No loss of signal
- Hybrid optical cable with fiber and copper wire
- PIN gold plated, shell gold plated
- Environmental Specifications: For Indoor use only;
- Operating temperature: -40°C to 70°C
- Minimum bending radius 20mm
- Max. tension force: 100N
- Powered via HDMI devices
- 4core OM3 Multimode Fiber (high speed data) and 7core copper cable
- Round cable Black PVC jacket
- RoHS 2.0 & REACH compliant
- Packing: package 1pc reel

NOTE:

- Supports computer resolutions to 4K@120Hz or 8K@60Hz 4:4:4



50M(max)±2%



MARK	DATE	ECON NO.	DESCRIPTION	REV.	DESIGN
△1					

UNLESS OTHERWISE SPECIFIED TOLERANCE				图号	日期	品名	单位	比例	页码	版本
ANG	TOL	DIM	TOL	制图	2022.01.19	HDMI 8K AM-DW-AM(W/OCC)	mm	1:1	1/1	1
.X	±3.0'	.X	±0.10	审核						
.XX	±2.0'	.XX	±0.05	核准						
.XXX	±1.0'	.XXX	±0.03							